



4 & 4.5 CUBIC YARD STAINLESS STEEL SALT & SAND SPREADERS



IDEAL FOR HEAVY DUTY MUNICIPAL & COMMERCIAL APPLICATIONS.

Gas Engine or Hydraulic Drive

Designed for dump bodies & flat bodies with a GVW chassis of 15,000 to 20,000 lbs. and is available with either hydraulic motor drive or 10-1/2 HP gas engine.

GENERAL:

- Self-contained hopper.
- Spreads free flowing materials sand and/or salt.
- Spread width of 4' to 30'.

MATERIAL HOPPER:

- 12 gauge 304 stainless steel with continuously welded seams.
- All hopper sides are formed with a continuous "J" channel profile for added rigidity and strength. Six (6) 12 gauge body gussets.
- Optimum material feed is maintained by hopper side walls sloped at 45°.
- Heavy-duty 4-section hinged top grate is standard. Bars are 1/4" diameter located on 3" center grid.
- Built-in four corner lift points.

CONVEYOR:

- 12-1/2" wide, all steel pintle chain conveyor with 1/4" x 1" crossbars on 4-5/8" centers.
- Replaceable 10 gauge stainless steel chain shields.
- Replaceable 10 gauge stainless steel conveyor floor.
- 10 gauge stainless steel inverted "V".
- Conveyor driven by 20:1 ratio worm gearbox utilizing tapered bearings.
- Conveyor chain is adjustable for chain take up, providing optimum performance and drive life.
- Chain drive and idler sprockets are 6-tooth cast sprockets keyed to 1-1/4" shafts.

SPINNER ASSEMBLY:

- Spinner chute has two adjustable internal baffles.
- Four (4) external baffles (3 adjustable, 1 fixed).
- 18" x 3/4" thick polyurethane spinner disc.
- Hydraulic model's chute utilizes four (4) spring loaded stainless steel quick detach pins for ease of: material unloading, tow hitch access and storage.

POWER SOURCE:

- Hydraulic Drive: Two independent hydraulic motors (15 GPM @ 1,500 PSI).
- Gas Engine: 10.5 horsepower Briggs & Stratton.

OPTIONAL EQUIPMENT:

- Nylon strap mounting kit.
- Tailgate latch kit.
- Liquid spray system, electric.
- Stainless steel D.O.T. spreader lightbar.

DISTRIBUÉ PAR / DISTRIBUTED BY: Phil Larochelle Équipement Inc. (418) 522-8222